

Specifications Guide



Certifications and Ratings:

- Fire safety rating smoke and flame spread criteria
 - L ASTM E84 testing
 - L NSF standard 7
 - L UL certification

Warranty:

- 50 year thermal warranty
- 10 year panel coverage
- 1 year warranty for all parts
- 5 year compressor motor warranty

Why SRC:

- World-class customer service and support
- Innovative solutions
- Nationwide delivery
- Short lead times
- Reputation for quality and integrity
- Custom designs

 Quote Today at:
srcrefrigeration.com

 800.521.0398

 sales@src.us



SCAN TO LEARN MORE

SRC Refrigeration custom manufactures extruded polystyrene (XPS) panels designed for commercial walk-in coolers and freezers. Tongue and groove profiles along with a cam-lock pocket are cut into the panels, creating an airtight seal in between wall sections. Our walk-in coolers can be tailored to suit your businesses temperature-controlled requirements, specifications and applications.



Panel Features:

- Extruded polystyrene foam (XPS)
- Cam-lock system with tongue and groove profile
- Metal skin finishes available:
 - L 24-gauge embossed pure zinc coated galvanized steel and 22-gauge stainless steel
 - L Colors available: white, black and natural
- Metal finish:
 - L Protective embossed epoxy finish

Panel Specifications	XPS Panel
Panel thickness	4"
Core density	4 lb/ft ³
R-Value per inch	
Cooler	7.2
Freezer	8.1
Standard panel lengths	8', 10', 12'
Single span length	12' unsupported ceilings
Max unsupported height	16' no supports
Average weight of a 4 x 8 panel	90lbs

